



PRODUCTS, INC.

10566 Plaza Drive, Whitmore Lake, MI 48189

E-Mail www.sales@fortechproducts.com

Phone (734) 449-8644

Fax (734) 449-8729

Product Data Sheet

Lubri-Gas

Solvent Refined High Viscosity Upper Cylinder Lubricant

Lubri-Gas is formulated for use in all Gasoline or Diesel engines at a recommended treatment level of 1 gallon to 500 gals (1oz. to 4 gallons of fuel), Lubri-Gas will provide the following performance features:

Lubrication

- Reduces friction heat and wear by providing full time lubrication to fuel system components, top cylinders, rings and valves
- Helps to prevent valve seat recession from low lead, no lead or oxygenated gasoline and gasohol
- Increases compression pressure, power and performance
- Improves fuel efficiency and reduces oil consumption

Detergency

- Cleans and prevents deposits on fuel injectors
- Prevents varnish and deposits in the entire fuel system
- Restores lost power
- Improves acceleration
- Reduces emissions
- Improved combustion

Stabilizer And Corrosion Inhibitors

- Prevents build-up of rust and corrosion from fuels stored over extended periods of time

Lubri-Gas is available at our Whitmore Lake, Michigan facility in 55 gallon drums, 300 gallon totes, 500 gallon totes, and bulk tanker truck.

Storage And Handling: See Material Safety Data Sheet Before Use. Use at room temperature. If frozen, allow to thaw completely prior to use. Do not expose to extreme high temperature due to drum rupture. Do not pressurize drum or reuse empty container.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 4/11/07

