


Hi-Lite Vanishing Oil

DESCRIPTION:

Hi-Lite Vanishing Oil is a solvent-based lubricant that is applied to Body-in-White panels by placing a thin film that facilitates a bright surface exposing any surface finish defects. Hi-Lite will evaporate from the panel shortly after application, providing the panel with a clean, dry surface.

This post is also available in: 

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

Appearance	Transparent Water White
Specific Gravity @ 60oF, ASTM D-1298	0.81
Pounds Per. Gallon, ASTM D-1298	6.72
Flash Point, ASTM D-93	~230°F
Viscosity, SSU @ 100°F, ASTM D-445	~2 cSt

FEATURES / BENEFITS:

- Non-Staining
- Easily Applied
- Easily Removed

MIX / APPLICATION & USE:

Hi-Lite Vanishing Oil

HEALTH & SAFETY:

Hi-Lite Vanishing Oil is available at our Brighton, Michigan facility in 55-gallon drums, 330 gallon totes and 5 gallon pails.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. Store at temperatures between 45° - 90°F. Do not expose to extreme high temperature due to container rupture. Do not pressurize drum or reuse empty container. Follow all safety regulations on label.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 4/14/2020