

TechDraw FT315-RTU

DESCRIPTION:

TechDraw FT315-RTU is water extendable ready-to-use lubricant, similar to a traditional Vanishing Oil, that provides a thin film of lubricant that facilitates a clean die release on both thin sheet and roll stock. The product may be applied by brush, roller, spray, dip tank, slush or flow coat.

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

| | |
|------------------------|--------------|
| Appearance | Clear Liquid |
| Density (g/mL) | 0.99 - 1.02 |
| Flash Point, ASTM D-93 | >232F |
| pH neat | 8.05 - 8.25 |

FEATURES / BENEFITS:

- Easily Applied
- Easily Removed with Water Dilutable Cleaner
- Compatible with Welding
- Non-Staining

APPROVALS:

MIX / APPLICATION & USE:

TechDraw FT315-RTU

HEALTH & SAFETY:

TechDraw FT315-RTU is available at our Brighton, Michigan facility in 55-gallon drums, 330 gallon totes and 5 gallon pails.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. Store at temperatures between 45° - 90°F. Do not expose to extreme high temperature due to container rupture. Do not pressurize drum or reuse empty container. Follow all safety regulations on label.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 1/13/2025