

TechDraw FT 905 Low Viscosity, Fine Blanking Lubricant

DESCRIPTION:

TechDraw FT 905 is a low-viscosity, straight petroleum oil-based metal forming and fine blanking lubricant formulated for high strength substrates. **TechDraw FT 905's** unique formulation of polymeric esters and extreme pressure chemistry can provide heavy duty lubrication, yet is easily removed with alkaline cleaners where clean surfaces are required in subsequent operations such as welding, coating, and plating. **TechDraw FT 905** provides superior performance with both ferrous and non-ferrous metals.

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

Appearance	Golden Translucent Lubricant
Specific Gravity @ 60F, ASTM D-1298	1.091
Density	9.1
Viscosity @ 40C (cSt)	44.7
Copper Corrosion	4C

FEATURES / BENEFITS:

- Heavy duty, low viscosity
- Easily removed with a low alkaline wash
- Low odor
- Easily sprayed

MIX / APPLICATION & USE:

TechDraw FT 905 is a straight oil designed to be used neat. Applications typically consist of spray, roll coat, brush or dip. Your application method must be designed to fulfill your desired lubricant film thickness. A Fortech Customer Representative will work with your team on a correct usage and application to serve your needs.

TechDraw FT 905 Low Viscosity, Fine Blanking Lubricant

HEALTH & SAFETY:

TechDraw FT 905 is available at our Brighton, Michigan facility in 55 gallon drums, 275 gallon totes, 330 gallon totes, and bulk tanker truck.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. If frozen, allow to thaw completely prior to use. Do not expose to extreme high temperature due to drum rupture. Do not pressurize drum or reuse empty container.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 10/28/2020