

TechKool FT 3000R Semi-Synthetic Coolant

DESCRIPTION:

TechKool FT 3000R is a moderate to heavy-duty semi-synthetic coolant for machining and grinding in a wide range of applications. **TechKool FT 3000R** provides lubrication and corrosion protection of a soluble oil, with the cleanliness and biostability of a synthetic. While providing outstanding protecting against ferrous corrosion it is also compatible with pure aluminum, brass, and copper. This product has an outstanding foam profile, even in high pressure systems and is hard water compatible.

TechKool FT 3000R will stop sump odors, give you exceptionally long sump life and a clean, comfortable, safe work environment for machine operators. Free of Boron, Triazine, Secondary Amines and Chlorinated Additives.

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

Appearance	Slight haze/yellow
pH diluted	9.0-9.5
Density	1.03 g/ml
RI Factor	x 2.5

FEATURES / BENEFITS:

- Metals: ferrous and non-ferrous metals, including high- or low-carbon steels, alloy steels, cast iron, nodular iron and gray iron, stainless steel, including automotive and aerospace grade aluminum alloys, titanium and exotic alloys
- Processes: Turning, Milling, Drilling, Tapping and Grinding
- Enhanced biological control
- In-process protection of machinery and parts
- Low operational cost
- Excellent corrosion protection
- Mild Odor

MIX / APPLICATION & USE:

Always add FT 3000R concentrate to the water and stir until uniformly mixed. Use premixed coolant as makeup to maintain performance. The makeup selected should balance the water evaporation rate with the coolant carryout rate. A qualified Fortech representative will work with your team to help achieve the most beneficial charge and makeup concentrations for your operation.

TechKool FT 3000R Semi-Synthetic Coolant

HEALTH & SAFETY:

TechKool FT3000R is available at our Brighton, Michigan facility in 5 gallon pails, 55 gallon drums, and 330 gallon totes.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. Store at temperatures between 45° - 90°F. Do not expose to extreme high temperature due to container rupture. Do not pressurize drum or reuse empty container. Follow all safety regulations on label.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 11/4/2022