

TechKool FT PG 30 Heat Transfer Fluid

DESCRIPTION:

TechKool FT PG 30 is an inhibited Propylene Glycol Fluid used to provide freeze and burst protection for hot and chilled, closed loop water systems while inhibiting the formation of corrosion.

Applications Include:

HVAC Systems

Process Cooling and Heating

Solar Heating

Refrigeration Warehouse Floor Heating

Thermal Energy Sources

Ice Rinks

Computer Cooling Systems

FEATURES / BENEFITS:

- Freeze and Burst Protection
- Reduces Corrosion
- Low Toxicity

MIX / APPLICATION & USE:

TechKool FT PG 30 should be diluted in water containing <50ppm hardness and <25ppm sulfate and chlorides. DI or distilled water is recommended.

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

| | |
|---------------------------|----------|
| Propylene Glycol | 29 |
| % wt Inhibitors and Water | 71 |
| pH of Solution | 8.9-10.2 |

TechKool FT PG 30 Heat Transfer Fluid

HEALTH & SAFETY:

TechKool FT PG 30 Heat Transfer Fluid is available at our Brighton, Michigan facility in 55-gallon drums, 330 gallon totes and 5 gallon pails.

Storage And Handling: See Safety Data Sheet Before Use.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 09/20/2022