


TechKut FT745 Non-Chlorinated Heavy-Duty Cutting Oil

DESCRIPTION:

Key Features: TechKut FT745 is a heavy-duty straight cutting oil designed with specialized polymers to allow for a variety of cutting operations. Its unique lubricity additives provide hydrodynamic and polar lubrication, outperforming other cutting oils. In addition, the excellent wetting properties make **TechKut FT745** capable of light forming operations. It is ideal for both ferrous and non-ferrous materials.

This post is also available in: 

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

Appearance	Clear Amber Oil
Density (lbs/gal)	7.76
Viscosity (cSt at 40°C)	150
Copper Corrosion	4B

FEATURES / BENEFITS:

- Non-Chlorinated
- Low Evaporation
- Excellent Corrosion Protection

MIX / APPLICATION & USE:

TechKut FT745 Non-Chlorinated Heavy-Duty Cutting Oil

HEALTH & SAFETY:

TechKut FT745 is available at our Brighton, Michigan facility in 55-gallon drums, 330 gallon totes and 5 gallon pails.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. Store at temperatures between 45° - 90°F. Do not expose to extreme high temperature due to container rupture. Do not pressurize drum or reuse empty container. Follow all safety regulations on label.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 4/9/2020