


TechPro FT RA-2 Release Agent

DESCRIPTION:

TechPro FT RA-2 is a synthetic elastomer lubricant used in a variety of applications in the automotive and appliance segments as a mandrel release agent. **TechPro FT RA-2** provides excellent thermal stability through its additive package, while being free of nitrites, chlorinated additives or heavy metals.

TechPro FT RA-2 can be used directly or diluted pending on the application, while being easily removable in water even at room temperature.

This post is also available in: 

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

Appearance	Hazy light-yellow liquid
Density (g/ml)	1.10 @25C
pH	9.5-11.5
Viscosity	238 - 262 cSt @ 40°C
Water Solubility	Soluble

FEATURES / BENEFITS:

- Excellent thermal stability
- Operator friendly, does not produce irritating fumes
- Little to no residue, easily cleaned with room temperature water

MIX / APPLICATION & USE:

TechPro FT RA-2 can be diluted or used in its concentrate form, applied directly to the mandrels. TechPro FT RA-2 can be applied using spray, dip, rollers or brush applications. Your Fortech Customer Sales Representative will work with you on a proper dilution and application set up.

TechPro FT RA-2 Release Agent

HEALTH & SAFETY:

TechPro FT RA-2 is available at our Brighton, Michigan facility in 55-gallon drums, 330 gallon totes and pails.

Storage And Handling: See Safety Data Sheet Before Use. Product be stored at temperatures between 45°F– 90°F. Do not expose to extreme high temperature due to container rupture. Do not pressurize drum or reuse empty container. Follow all safety regulations on label.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 7127/2024