


Hydraulic Oil 32 AW, 46AW, 68AW

DESCRIPTION:

Fortech Products TechLube Hydraulic Oils, available in ISO Grades 32 through 68, provide excellent performance in hydraulic systems and air compressors, industrial bearings, machine tools, hoists, and circulating, splash, bath and ring systems for bearings and gears. Our hydraulic oils provide foam inhibition, rust and corrosion protection, good thermal stability, excellent water separation, and excellent oxidation stability. These oils, designed with paraffinic base oils, provide an anti-wear film which helps minimize metal to metal contact. Sludge deposits are also controlled with oxidation inhibitors.

This post is also available in: 

TYPICAL PROPERTIES (NOT SPECIFICATIONS):

Appearance	Amber Oil
Density	7.21
Viscosity (Kinematic, 40C)	Varies based on oil grade

FEATURES / BENEFITS:

- Excellent Anti-Wear Properties
- Good Thermal Stability
- Rust and Corrosion Protection
- Quick Water Separation
- Excellent Foam Suppressant

MIX / APPLICATION & USE:

Hydraulic Oil 32 AW, 46AW, 68AW

HEALTH & SAFETY:

Hydraulic Oils 32AW, 46AW, and 68AW are available at our Brighton, Michigan facility in 55-gallon drums, 330 gallon totes and 5 gallon pails.

Storage And Handling: See Safety Data Sheet Before Use. Use at room temperature. Store at temperatures between 45°-90°F. Do not expose to extreme high temperature due to container rupture. Do not pressurize drum or reuse empty container. Follow all safety regulations on label.

Non-Warranty: While the information and recommendations sent forth herein are believed to be accurate as of the date thereof, Fortech Products, Inc. makes no warranty with respect thereto and disclaims all liability for reliance therein.

Last Updated: 4/15/2020